

`input.sh`

CentOS / Fedora / RHEL Package Management

Aleksandar Todorović

June 2020

CC BY-SA 4.0

rpm

Syntax	Description
<code>rpm -i <package_name>.rpm</code>	Installs a new package or updates it if it's already installed.
<code>rpm -U <package></code>	Upgrades a package. If it's not installed, it will install it.
<code>rpm -F <package_name></code>	Upgrades a package only if it's already installed.
<code>rpm -e <package_name></code>	Removes (erases) a package.
<code>rpm -qa</code>	Lists installed packages.
<code>rpm -qi <package_name></code>	Displays info about the package (query info).
<code>rpm -ql <package_name></code>	Displays files installed by the package (query list).
<code>rpm -qip <package_name>.rpm</code>	Displays info about the package that's not currently installed.
<code>rpm -qlp <package_name>.rpm</code>	Displays files that will be installed if you decide to install a package.
<code>rpm -qf /path/to/file</code>	Displays the package to which the specified file belongs to.

yum

Syntax	Description
<code>yum search <package_name></code>	Searches for a package.
<code>yum install <package_name></code>	Installs a package.
<code>yum update <package_name></code>	Updates specific package to its latest version.
<code>yum update</code>	Updates all the installed packages to their latest version.
<code>yum whatprovides <file_name></code>	Finds a package that provides file name specified.
<code>yum info <package_name></code>	Provides info about the package.
<code>yum repolist all</code>	Shows all available repositories.

yum-config-manager

Syntax	Description
<code>yum-config-manager --add-repo https://example.com/repo</code>	Adds a repository from a specified URL.
<code>yum-config-manager --enable repository</code>	Enables a repository.
<code>yum-config-manager --disable repository</code>	Disables a repository.